Request to Develop or Modify Reliability Rules and Requirements (NYSRC Policy No. 1-11) Submit request to herb@poweradvisorsllc.comvia the NYSRC site www.nysrc.org

oubt request	
Item	Information
1. PRR No. & Title of Reliability	PRR 140 Modification of A.1: Establishing NYCA Installed Reserve Margin
Rule or Requirement change	Requirements
2. Rule Change Requester	
Information	DDC.
Name	RRS
Organization	
2 November	Devicion
3. New rule or revision to existing rule?	Revision
ruier	
4. Need for rule shange including	To clarify A.1 requirements and to revise to be consistent with NPCC Directory 1
4. Need for rule change, including advantages and disadvantages	resource adequacy requirements.
advantages and disadvantages	resource adequacy requirements.
5. Related NYSRC rules	A.2
5. Related Wiske Fules	N.2
6. Section A – Reliability Rule	
Elements	
Reliability Rule	An Installed Reserve Margin (IRM) requirement for the NYCA for each Capability
, , , , ,	Year shall be established. (No changes)
Associated NERC & NPCC	NPCC Directory 1
Standards and Criteria	NFCC Directory 1
3. Applicability	NYSRC, NYISO, LSEs
3. Аррисавшту	NTSNC, NTISO, ESES
7. Section B – Requirements	
Requirements	R12. The NYSRC shall annually perform and document an analysis periodically
equee	perform resource adequacy studies toto be used for establishing the NYCA
	Installed Reserve Margin (IRM) requirement for the following Capability Year.
	The IRM analysis shall:update the required statewide IRM. A report shall be
	prepared providing the assumptions, procedures, and results of the study.
	P1 1 The AVCOC shall Drahahilistically establish the 1004 requirement for
	R1.1 The NYSRC shall Probabilistically establish the IRM requirement for
	the NYCA such that the probability (or risk) of disconnecting any firm load
	due to resource deficiencies shall be, on average, not more than once in
	ten years. Compliance with this criterion shall be evaluated
	probabilistically, such that the loss of <i>load</i> expectation (LOLE) of
	disconnecting firm load due to resource deficiencies shall be, on average,
	no more than 0.1 days per year. This evaluation shall make due allowances
	for demand uncertainty, scheduled outages and deratings, forced outages
	and deratings, assistance over interconnections with neighboring control
	areas, NYS Transmission System emergency transfer capability, and
	capacity and/or load relief from available operating procedures.
	capacity and/or load relief from available operating procedures.
	R1.2 Utilize the methodology and modeling parameters for
	establishing NYCA IRM requirements, and a timeline for the study
	process, as described in NYSRC Policy 5, "Procedure for Establishing NYCA
	N

Formatted: Normal, Left, Indent: Left: 0", Hanging: 0.38", Line spacing: single, Tab stops: Not at 1"

Formatted: Font: 10 pt

Formatted: Indent: Left: 0"

Formatted: Font: (Default) +Body (Calibri)

	Installed Capacity Requirements."
	R1.3 Prepare a technical report documenting the assumptions, models,
	methodology, and results of the IRM study.
8. Section C – Compliance	(To be provided later)
Elements	
 Measures 	
Levels of Non-Compliance	
Compliance Monitoring	
Process (See Policy 4):	
3.1 Compliance	
Monitoring Responsibility	
3.2 Reporting Frequency	
3.3 Compliance Reporting	
Requirements	
9. Implementation Plan	
10. Comments	
11. Date Rule Adopted	
12. PRR Revision Dates	12/19/17

Formatted: Font: 10 pt