NYCA IRM Requirement Study 2026-2027 Preliminary Base Case (PBC) Model Assumptions Matrix

Draft V0.0

NYSRC

Installed Capacity Subcommittee Meeting #300 February 5, 2025

Load Forecast

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
1	Peak Load Forecast (Preliminary Base Case – Parametric & Sensitivities)	2024 Gold Book ¹ NYCA: 31,832.2 MW NYC: 11,227.5 MY LI: 5077.9 MW G-J: 15,298.5 MW (Attachment A1)			
2	Peak Load Forecast (Final Base Case)	October 2024 Fcst NYCA: 31,649.7 MW ¹ NYC: 11,043.9 MW LI: 5,092.1 MW G-J: 15,205.1 MW			
3	Load Shape (Multiple Load Shape)	Bin 1-2: 2013 Bin 3-4: 2018 Bin 5-7: 2017			
4	Load Forecast Uncertainty (LFU)	Zonal Model to reflect current data with input from Con Ed and LIPA. (Attachment A2)			
5	LFU Winter	Attachment A3			

¹ Behind-the-Meter Net Generation (BTM:NG) resource loads have been incorporated into these numbers.

 $^{\rm 2}$ The loads associated with the BTM:NG program need to be added to these values.

Generation Parameters

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
6	Existing Generating Unit Capacities	2024 Gold Book Values. Use min. (DMNC vs. CRIS) capacity value			
7	Proposed New Units (Thermal) and re-ratings	47.0 MW summer re-rating for Thermal resources (Attachment B1)			
8	Deactivations and Removals ³	165.4 MW unit deactivations (Attachment B2)			
9	Forced and Partial Outage Rates	Five-year (2019-2023) GADS data for each unit represented. Those units with less than five years – use representative data. (Attachment C)			
10	Planned Outages	Planned Outages are removed from the IRM study			

³ Negative values in the 'SUMMER CRIS (MW)' column represent units that were previously expected to deactivate due to the NYSDEC "Peaker Rule" requirements for 2023 but did not deactivate. Therefore, they were reinstated in the 2024-25 IRM Study.

Generation Parameters

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
11	Summer Maintenance	Nominal 50 MW – divided equally as 2 negative 25MW units in Load Zones J and K			
12	Combustion Turbine Derates	Derate based on temperature correction curves provided			
13	Existing and Proposed New Wind Units	0 MW of offshore wind capacity additions 2,566.20 MW of qualifying wind. (Attachment B3)			
14a	Land-Based Wind Shape	Actual hourly plant output over the period 2019-2023. New units will use zonal hourly averages or nearby units.			
14b	Offshore Wind Shape	Normalized offshore wind shapes as published by NYISO over the period 2017-2021			
15	Existing and Proposed New Solar Resources	267 MW of utility-scale solar capacity additions totaling 571.4 MW of qualifying solar capacity. (Attachment B3)			
16	Solar Shape	Actual hourly plant output over the period 2019-2023. New units will use zonal hourly averages or nearby units.			

Generation Parameters

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
17	BTM:NG Program	No new BTM:NG resources, total of 170.6 MW (Attachment B5)			
18	Small Hydro Resources	Actual hourly plant output over the period 2019-2023			
19	Large Hydro	Probabilistic model based on five years of GADS data (2019-2023)			
20	Landfill Gas (LFG)	Actual hourly plant output over the period 2019-2023.			
21	New Energy Storage	0 MW of new battery storage scheduled.			
21	Resources (ESRs)	20 MW of total battery storage modeled.			
22	Energy Limited Resources	Based upon elections made by August 1 st , 2024			
	(ELRs)	ES and small EL3 output limitations lifted at HB14			

Transactions- Imports and Exports

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
23	Capacity Purchases	Existing Rights: PJM – 1,013 MW HQ – 1,190 MW All contracts modeled as equivalent contracts.			
24	Capacity Sales	Long Term firm sales Summer 266.6 MW			
25	Forward Capacity Market (FCM) Sales from a Locality ⁴	No sales modeled within study period			
26	Wheels through NYCA	300 MW HQ to NE equivalent contract			
27	New Unforced Capacity Deliverability Rights (UDRs)	No new UDRs Identified			
28	New External Deliverability Rights (EDRs)	No new EDRs Identified			

⁴ Final FCM sales that will materialize are unknowable at the time of the IRM study. To reflect the impact these sales have on reliability, the NYISO applies a Locality Exchange Factor in the market.

Topology

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
29	Interface Limits	Updates to the Central East forward limits, and West-Central reverse limit			
30	New Transmission	None Identified			
31	AC Cable Forced Outage Rates	All existing Cable EFORds for NYC and LI to reflect most recent ten - year history (2014-2023) (Attachment E4)			
32	UDR Line Unavailability	Ten-year history of forced outages (2014-2023)			

Emergency Operating Procedures

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
33	Special Case Resources (SCRs)	July 2024 – 1,486.7 MW based on registrations and modeled with maximum capacity of 1,280.8 MW derated by hourly response rates. Utilize a new energy limited resource (ELR) functionality to model SCRs as duration limited resources with hourly response rates and limited to one call per day. Monthly variation based on historical experience.			
34	Other Emergency Operating Procedures (EOPs)	400 MW of 10-min reserves maintained at load shedding Voluntary Curtailment and Public Appeals limited to 3 calls per year 804.6 MW of non-SCR/non- EDRP resources (Attachment D)			
35	EOP Structure	10 EOP steps modeled			

External Control Areas

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
36	MſĄ	Load and capacity data will be provided by PJM/NPCC CP-8 Data may be adjusted per NYSRC Policy 5. (Attachment E)			
37	ISONE, Quebec, IESO	Load and capacity data will be provided by ISONE/NPCC CP-8 Data may be adjusted per NYSRC Policy 5. (Attachment E)			
38	External Adjustments per Policy 5	If needed, add load to externals proportional to existing excess capacity.			
39	Reserve Sharing	All NPCC Control Areas indicate that they will initially share reserves equally among all members and then non-members.			
40	Emergency Assistance	Statewide emergency assistance allowed from neighbors: Bin 1: 1,470 MW Bin 2: 2,600 MW Bin 3-7: 3,500 MW Individual interface limits and PJM cables are also reduced by Bin (Attachment E5)			

Miscellaneous

#	Parameter	2025 Model Assumptions	2026 Model Assumptions	Basis for Recommendation	Model Change
41	MARS Model Version	4.14.2179			
42	Environmental Initiatives	No new rules for 2025-2026 Capability Year			


NYCA Summer Load Forecast Coincident and Non-Coincident Peak: 2025-2026 Final Base Case (FBC) and 2026-2027 Preliminary Base Case (PBC)

	2025-2026 FBC												
Area	А	В	С	D	E	F	G	Н	I	J	K	NYCA	G_J
NCP - Forecast	3,089.2	1,971.1	2,675.8	721.3	1,326.2	2,293.8	2,286.2	614.2	1,352.7	11,043.9	5,092.1		
CP - Forecast	2,926.8	1,925.4	2,596.5	693.0	1,291.2	2,239.2	2,235.5	600.7	1,323.1	10,802.3	5,016.0	31,649.7	
G-J Peak - Forecast							2,271.8	610.5	1,344.7	10,978.1			15,205.1

	2026-2027 PBC													
Area	А	В	С	D	E	F	G	Н	I	J	K	NYCA	G_J	
NCP - Forecast													-	
CP - Forecast														
G-J Peak - Forecast														

	Delta												
Area	А	В	С	D	E	F	G	Н	I	J	K	NYCA	G_J
NCP - Forecast													
CP - Forecast													
G-J Peak - Forecast													

NYCA Summer Load Forecast Uncertainty Model: 2025 and 2026



Load Forecast 2025

Bin	Bin z	Bin Probability	A-E	F&G	H&I	J	к
Bin 1	2.74	0.62%	113.93%	110.69%	110.18%	108.88%	116.62%
Bin 2	1.79	6.06%	109.54%	107.86%	107.34%	105.42%	111.14%
Bin 3	0.89	24.17%	104.86%	104.04%	103.09%	101.61%	105.52%
Bin 4	0.00	38.29%	100.00%	99.46%	97.81%	97.51%	100.00%
Bin 5	-0.89	24.17%	95.00%	94.29%	91.70%	93.12%	94.48%
Bin 6	-1.79	6.06%	89.91%	88.61%	84.93%	88.45%	88.89%
Bin 7	-2.74	0.62%	84.79%	82.53%	77.65%	83.48%	83.27%

Load Forecast 2026

NYCA Winter Load Forecast Uncertainty Model: 2026

NYCA Winter LFU Model (2025)

Bin	Bin z	Bin Probability	NYCA
Bin 1	2.74	0.62%	110.37%
Bin 2	1.79	6.06%	106.37%
Bin 3	0.89	24.17%	102.75%
Bin 4	0.00	38.29%	99.42%
Bin 5	-0.89	24.17%	96.29%
Bin 6	-1.79	6.06%	93.30%
Bin 7	-2.74	0.62%	90.41%

New Thermal Units and Unit Re-Ratings

	New Thermal Units and Unit Re-r							
Project or Generator Name	Zone	2025 Gold Book (MW) CRIS	2025 Gold Book (MW) DMNC	New or Incremental (MW)	2026 MARS Model (MW)			
		New Uni	ts					
Total New Units and Uprates (

To be updated for 2026-2027 IRM Study

Attachment B2

Deactivations and Removals

Unit Removal since 2026-2027 IRM Study							
Generator Name	Туре	Zone	SUMMER CRIS (MW)				
Total Removals							

New Intermittent Resources

New Intermittent Units							
Resource	Zone	CRIS (MW)	Summer Capability (MW)	MARS Modeled Capacity			
Wind							
Total Wind							

Solar						
Total Solar						

New Energy Storage Resources

Energy Storage							
Resource	Zone	CRIS (MW)	Summer Capability (MW)	Lesser of Summer Capability VS CRIS			
	New Battery Units						
Total New Energy Storage							


Resources in the Behind-the-Meter Net Generation (BTM:NG) Resource Program

Attachment B5 - Units in the Behind-the-Meter Net Generation Resource Program*								
Generator Name	Zone	Resource Value (MW)⁵	Peak Load Adjustment (MW) ⁶					
Existing:								
Total BTM-NG								


*The IRM study independently models the generation and load components of BTM:NG Resources.

⁵ Based on adjusted Dependable Maximum Gross Capability (DMGC) value.

⁶ Based on Average Coincident Host Load (ACHL).



NYCA Five Year Derating Factors – All Resources



NYCA Five Year Derating Factors - Intermittent Power Resources



Emergency Operating Procedures

Step	Procedure	2025 IRM MW Value	2026 IRM MW Value
1	Special Case Resources – Load, Gen	1,486.7 MW Enrolled / 1,280.8 MW Modeled	
2	5% manual voltage Reduction	63.38 MW	
3	Thirty-minute reserve to zero	655 MW	
4	Voluntary industrial curtailment	260.74 MW Limited to 3 calls per year	
5	General Public Appeals	74 MW Limited to 3 calls per year	
6	5% remote voltage reduction	406.49 MW	
7	Emergency Purchases	Varies	
8	Ten-minute reserves to zero	910 MW (400 MW maintained at load shedding)	
9	Customer disconnections	As needed	
10	Adjustment used if IRM is lower than technical study margin	As needed	

To be updated for 2026-2027 IRM Study

Attachment E1

IRM Topology

ISO-NE 14 Bubble Model

To be updated for 2026-2027 IRM Study

Attachment E3

PJM Bubble Model

Cable Outage Rate						
2018-22* (5-year average)	2014-23 (10-year average)					
5.36%	5.31%					

The facilities included in these averages are VFT, HTP, Dunwoodie-South, Y49/Y50, CSC, Neptune, Norwalk-Northport and A-Line.

*The 10-year average data is not available for the 2024-2025 IRM study

	2025-2026 IRM Dynamic Emergency Assistance (EA) Interface Group Limits (MW)									
Area	Bin 1	Bin 2	Bin 3	Bin 4	Bin 5	Bin 6	Bin 7			
IESO	550	660	750 860 Maximum EA (1,950)							
ISONE	50	540	1,000 1,530 Maximum EA (1,804)							
PJM*	580	1,110			Maximum EA (1,415)					
HQ	Q Maximum EA (280)									
Total EA**	1,470	2,600	Maximum EA (3,500)							

	Dynamic EA PJM Cable Limits (MW)***								
Area	Bin 1	Bin 2	Bin 3 Bin 4 Bin 5 Bin 6 Bin 7						
HTP	90	173	Maximum EA (660)						
Neptune	90	173	Maximum EA (660)						
VFT	43	83	Maximum EA (315)						
A Line	14	28		Maximum EA (105)					

* PJM ties limits are only applicable to A, C, and G ties, and individual cables are derated separately, in proportion to the Bin 1 and Bin 2 PJM interface group limits listed above

** The total EA limit from all ties are derived from a separate regression analysis and may not match the sum of all group tie limits in each LFU bin

******* Limiting EA, does not affect contract capacity over UDRs

SCR Determinations 2025-2026 and 2026-2027 IRM Studies

	SCR Performance for 2026-2027 IRM Study								
Cuper Zenes	Response Rate (%) by Hour of SCR Activation								Superzonal ACL to CBL
Super Zones	SCR Enrollments (MW)	Event Hour 1	Event Hour 2	Event Hour 3	Event Hour 4	Event Hour 5	Event Hour 6	Event Hour 7	Translation Factor (%)
A - E									
F									
G - I									
J									
к									
All Zones									

	SCR Performance for 2025-2026 IRM Study									
0	Response Rate (%) by Hour of SCR Activation								Superzonal ACL to CBL	
Super Zones	er Zones SCR Enrollments (MW)		Event Hour 2	Event Hour 3	Event Hour 4	Event Hour 5	Event Hour 6	Event Hour 7	Translation Factor (%)	
A - E	783.4	77.85%	83.57%	82.28%	70.24%	69.18%	0%	0%	93.45%	
F	103.5	75.94%	82.20%	85.24%	86.18%	85.54%	70.40%	66.99%	90.58%	
G - I	90.6	58.45%	67.53%	70.20%	71.94%	73.63%	71.48%	0%	84.07%	
J	478.7	55.04%	60.60%	65.47%	67.78%	68.80%	66.09%	0%	74.29%	
к	30.6	49.71%	56.72%	62.12%	64.63%	64.66%	63.36%	52.65%	76.11%	
All Zones	1,486.7	62.01%	68.39%	71.35%	69.61%	69.93%	66.38%	58.14%		

7. These values represent no growth from July ICAP based enrollments for the previous year. Differences in data in this column are due to software rounding updates since the 2023-2024 IRM study. Updated data aligns with 2023 Gold Book values of the Previous year. Differences in data in this column are due to software rounding updates since the 2023-2024 IRM study. Updated data aligns with 2023 Gold Book values of the Previous year. Differences in data in this column are due to software rounding updates since the 2023-2024 IRM study. Updated data aligns with 2023 Gold Book values of the Previous year. Differences in data in this column are due to software rounding updates since the 2023-2024 IRM study. Updated data aligns with 2023 Gold Book values of the Previous year.

9. The SCR Adjustment factor captures two different performance derates: (1) Calculated Translation Factor (TF) between ACL and CBL values and (2) the Fatigue Factor (FF=1.00).

Attachment G Wind Units Modeled

Wind							
Resource	Zone	CRIS (MW)	Summer Capability (MW)	MARS Modeled Capability**			
Arkwright Summit Wind Farm [WT]	A	78.4	78.4	78.4			
Ball Hill Wind [WT]	A	100.0	107.5	100.0			
Bliss Wind Power [WT]	A	100.5	100.5	100.5			
Baron Winds [WT]	С	300.0	121.8	121.8			
Canandaigua Wind Power [WT]	С	125.0	125.0	125.0			
Eight Point Wind Energy Center [WT]	С	101.2	111.2	101.2			
High Sheldon Wind Farm [WT]	С	112.5	118.1	112.5			
Howard Wind [WT]	С	57.4	55.4	55.4			
Orangeville Wind Farm [WT]	С	94.4	93.9	93.9			
Wethersfield Wind Power [WT]	С	126.0	126.0	126.0			
Altona Wind Power [WT]	D	97.5	97.5	97.5			
Chateaugay Wind Power [WT]	D	106.5	106.5	106.5			
Clinton Wind Power [WT]	D	100.5	100.5	100.5			
Ellenburg Wind Power [WT]	D	81.0	81.0	81.0			
Jericho Rise Wind Farm [WT]	D	77.7	77.7	77.7			
Marble River Wind [WT]	D	215.2	215.2	215.2			
Bluestone Wind [WT]	E	124.2	111.8	111.8			
Hardscrabble Wind [WT]	E	74.0	74.0	74.0			
Madison Wind Power [WT]	E	11.5	11.6	11.5			
Maple Ridge Wind [WT01]	E	231.0	231.0	231.0			
Maple Ridge Wind [WT02]	E	90.7	90.8	90.7			
Munnsville Wind Power [WT]	E	34.5	34.5	34.5			
Number 3 Wind Energy [WT]	E	105.8	103.9	103.9			
Roaring Brook [WT]	E	79.7	79.7	79.7			
South Fork Wind Farm (Offshore)	К	136.0	136.0	136.0			
Total		2,761.20	2,589.50	2,566.20			

Wind Units Not Currently Participating in ICAP Market

Wind									
Resource	Zone	Nameplate (MW)	CRIS (MW)	Summer Capability (MW)	MARS Modeled Capacity				
Cassadaga Wind [WT]	А	126.5	126.0	0.0	0.0				
Erie Wind [WT]	А	15.0	0.0	0.0	0.0				
Steel Wind [WT]	А	20.0	0.0	0.0	0.0				
Fenner Wind [WT]	С	30.0	30.0	0.0	0.0				
Marsh Hill Wind Farm [WT]	С	16.2	0.0	0.0	0.0				
Copenhagen Wind [WT]	E	79.9	79.9	0.0	0.0				
Total		287.6	235.9	0.0	0.0				

Solar Units Modeled

	Solar							
Resource	Zone	CRIS (MW)	Summer Capability (MW)	Lesser of Summer Capability vs. CRIS				
Janis Solar [PV]	С	20.0	20.0	20.0				
Morris Ridge Solar Energy Center	С	177.0	177.0	177.0				
Puckett Solar [PV]	С	20.0	20.0	20.0				
Albany County	F	20.0	20.0	20.0				
Albany County II	F	20.0	20.0	20.0				
Branscomb Solar [PV]	F	20.0	20.0	20.0				
Darby Solar [PV]	F	20.0	20.0	20.0				
East Point Solar	F	50.0	50.0	50.0				
Grissom Solar [PV]	F	20.0	20.0	20.0				
High River Solar	F	90.0	90.0	90.0				
Pattersonville Solar [PV]	F	20.0	20.0	20.0				
Regan Solar [PV]	F	20.0	20.0	20.0				
ELP Stillwater Solar [PV]	F	20.0	20.0	20.0				
Calverton Solar Energy Center [PV]	к	22.9	22.9	22.9				
Long Island Solar Farm [PV]	к	31.5	31.5	31.5				
Total		571.4	571.4	571.4				

Solar Units Not Modeled

Solar							
Resource	Zone	CRIS (MW)	Summer Capability (MW)	Lesser of Summer Capability vs. CRIS			
Shoreham Solar [PV]*	К	25.0	0.0	0.0			
Total		25.0	0.0	0.0			

*Unit provides power at the distribution rather than at the transmission level.

Landfill Gas (LFG) Units Modeled

	LFG							
Resource	Zone	CRIS (MW)	Summer Capability (MW)	Lesser of Summer Capability VS CRIS				
CHAFFEE [IC]	A	6.4	6.4	6.4				
Model City Energy LFGE [IC]	A	5.6	5.6	5.6				
Modern LFGE [IC]	A	6.4	6.4	6.4				
Hyland LFGE [IC]	В	4.8	4.8	4.8				
Mill Seat [IC]	В	6.4	6.4	6.4				
Broome 2 [IC]	С	2.0	2.1	2.0				
Broome LFGE [IC]	С	2.1	2.4	2.1				
High Acres Group [IC] (23767)	С	9.6	9.6	9.6				
Ontario LFGE [IC]	С	11.2	11.2	11.2				
Seneca Energy Group [IC] (23797)	С	17.6	17.6	17.6				
Clinton LFGE [IC]	D	6.4	6.4	6.4				
DANC LFGE [IC]	E	6.4	6.4	6.4				
Oneida-Herkimer LFGE [IC]	E	3.2	3.2	3.2				
Colonie LFGTE [IC]	F	6.4	6.4	6.4				
Fulton County Landfill [IC]	F	3.2	3.2	3.2				
Albany LFGE	F	4.5	5.6	4.5				
Totals		102.2	103.7	102.2				

Landfill Gas (LFG) Units Not Modeled

LFG							
Resource	Zone	CRIS (MW)	Summer	Lesser of Summer Capability VS CRIS			
			Capability (MW)	Lesser of Summer Capability VS Citis			
Chautauqua LFGE	А	9.6	0.0	0.0			
Synergy Biogas	В	2.0	0.0	0.0			
Madison County LFGE [IC]	E	1.6	0.0	0.0			
Total		13.2	0.0	0.0			

Assumption Matrix History

Date	Ver	Preliminary Base Case	Date	Ver	Final Base Case
02/05/2025	V0.0	Preliminary assumptions without attachments			

Draft